



Product Data Sheet

Rim Drive Cable Reeler



Dual Rim Drive Cable Reeler with variable speed hydraulic power pack.

- This cable reeler is designed with a fully adjustable frame that will accommodate cable reels from 60" to 120" diameter, and 48" to 84" wide.
- Maximum payload is 25,000 lbs (reel and cable combined)
 - Static weight of reeler stand – 1000 lbs
- Rim Drive system is designed to easily adjust to accommodate different sized cable reels
 - Variable speed drive from 1 RPM – 10 RPM



This unit is also our standard rental unit model. Each rental includes the reeler frame, hydraulic power pack, and one certified spindle for your specific requirements.

Hydraulic Power Pack Specifications:

- 15-25 gallon reservoir
- Internal drip tray on every unit
- Directional control valve with integrate flow control and pressure regulator
- Electric Power Pack includes 7.5-10HP, 208/230V Single phase motor with 3.8 GPM hydraulic pump rated 2000 PSI



• Quick coupling connections from hydraulic unit to rim drive unit for easy set up

Mine Cable Services Corporation 7731 - 16th Street NW, Edmonton, Alberta, Canada, T6P 1M1
Phone. (780) 439-1113 Website: minecableservices.ca Email: sales@minecableservices.ca