## **Product Data Sheet**

Cable Safety S-Hooks

Cable Safety S-Hooks suspend cables, wires, hoses, and similar materials to keep walkways, stairs, and working areas neat and organized.

With a variety of applications, Cable Safety S-Hooks are used in daily operations in construction, oil and gas, refineries, minesite operations, shippards and container ports. Cable Safety S-Hooks are also widely used in the transport industry to hang and organize rigging equipment while not in use.





## **Product Features and Benefits:**

- S-Hooks DO NOT conduct electricity.
- Proven industry technology with over 20 years' experience.
- Eliminates use of tie-wraps for unsafe cable installation.
- Manufactured from strong and durable glass reinforced polyester materials.
- Available in a variety of sizes: 6", 9", 12" 15"
- Maximum load ratings: 40kg to 265kg (88lbs to 584lbs)
- Standard color options include yellow or glow-in-the-dark to provide extra visibility at night. Custom colors available upon request.
- Extreme Model S-Hooks are fire retardant & UV protected.
- Working temperatures: -20°C up to 200°C (-4°F up to 392°F).





Canada 780-439-1113 Toll Free 1-800-663-2889

> Panamá +507-389-7990

## Cable Safety S-Hooks

Easy to use due to their simple s-shape design, Cable Safety S-Hooks increase safety while reducing workplace accidents by organizing and suspending hoses, cables, and work gear off the floor in common foot traffic and work areas.



Product Specifications and Ordering Information:					
Catalogue Number:	Size:	Cable Opening Size:		Maximum Load:	Weight:
		Тор:	Bottom:	Maximum Load.	weight.
CS-6-Y-FR-UV	6"	1.1"	1.6"	40 kg	40 grams
CS-6-GID-FR-UV		(2.7 cm)	(4.0 cm)	(88 lbs.)	(0.06 lbs.)
CS-9-Y-FR-UV	9"	1.5"	2.6"	55 kg	103 grams
CS-9-GID-FR-UV		(3.9 cm)	(6.6 cm)	(121 lbs.)	(0.23 lbs.)
CS-12-Y-FR-UV	12"	2.1"	3.5"	190 kg	292 grams
CS-12-GID-FR-UV		(5.4 cm)	(8.9 cm)	(418 lbs.)	(0.64 lbs.)
CS-15-Y-FR-UV	15"	2.5"	4.5"	265 kg	518 grams
CS-15-GID-FR-UV		(6.4 cm)	(11.4 cm)	(584 lbs.)	(1.14 lbs.)

Colors: Standard colors are Yellow (Y) or Glow-in-the-dark (GID)

Custom Colors are available upon request

UV: Stabilized, guaranteed 10 years-under normal usage conditions FR: Flame Retardant, UL Recognized, 94V-0 Flame Class Rating (3) Cold Fatigue: Protection in cold weather environment (-20° C)





Canada 780-439-1113 Toll Free 1-800-663-2889